

Microsoft Word interface showing a document with 12 numbered steps for applying blacktop sealer. The document is titled "MUST RULES?". The steps are:

1. A long-handled pushbroom or rooting brush is used to spread the coating evenly over the entire area.
2. Care should be taken to make certain the entire surface is uniformly wet, though puddles should be swept away if water collects in low spots.
3. Greasy areas and oil slicks should be scraped up, then scrubbed thoroughly with a detergent solution.
4. With most brands there are just three steps to follow.
5. In most cases one coat of sealer will be sufficient.
6. The application of blacktop sealer is best done on a day when the weather is dry and warm, preferably while the sun is shining on the surface.
7. This should not be applied until the first coat is completely dry.
8. First sweep the surface absolutely clean to remove all dust, dirt, and foreign material.
9. To simplify spreading and to ensure a good bond, the surface of the driveway should be wet down thoroughly by sprinkling with a hose.
10. However, for surfaces in poor condition a second coat may be required.
11. The blacktop sealer is next stirred thoroughly and poured on while the surface is still damp.
12. The sealer should be allowed to dry overnight (or longer if recommended by the manufacturer) before normal traffic is resumed.

Handwritten red annotations include the title "MUST RULES?", a large red oval around the right side of the list, and a red arrow pointing down from the top of the oval to the bottom.

Page: 1 of 1 Words: 243 100% 12:26 PM 10/10/2012